

SHRINK TAPE
 FOR SECURING YOUR PRODUCTS



Our range of shrink tapes allow you to maintain your film before sealing and also to secure any fragile areas of film. The quality of the adhesive as well as the strength of the material make it possible to work under any conditions.

«Shrink tape» is a professional term used to define a type of adhesive with a polyethylene backing and a heat-resistant adhesive. Nevertheless, this tape does not have the same characteristics as shrink-wrap and cannot tolerate so much heat.

Our shrink tapes are available in two widths: 50 and 100 mm. The 50 mm enables the film to be held before sealing and to secure vents. The 100 mm is useful for repairing holes in the film, protecting the film from protruding parts and securing zipped doors.

These tapes can be easily repositioned in the first few minutes after they are applied, but after about 15 minutes it is very difficult to remove them.

Their adhesive mass works on dry and clean materials, therefore areas in contact with the tape must be cleaned to improve adhesion.

TECHNICAL TABLE

Item code	Width 50mm : TapeSH50W Width 100mm : TapeSH100W
Width x Length	2" x 108 ft / 4" x 108 ft 50 mm x 33 m / 100 mm x 33 m
Sales units	Box of 24 / Box of 12
Tape thickness	0,20mm = 200µ
Mechanical resistance	27 N/cm (breaking load)
Temperature resistance	-5°C to +50°C

EQUIPMENT SOLD SEPARATELY



RIPACK 3000



SAFETY CUTTERS



WIDE SHRINK-WRAP

