

SHRINK TAPE
 FOR SECURING YOUR PRODUCTS



Our range of notched shrink tapes allow you to maintain your film before sealing and also to secure any fragile areas of film. The quality of the adhesive as well as the strength of the material make it possible to work under any conditions.

«Shrink tape» is a professional term used to define a type of adhesive with a polyethylene backing and a heat-resistant adhesive. Nevertheless, this tape does not have the same characteristics as shrink-wrap and cannot tolerate so much heat.

Our notched shrink tapes are available in two widths: 48 and 96 mm. The 48 mm enables the film to be held before sealing and to secure vents. The 96 mm is useful for repairing holes in the film, protecting the film from protruding parts and securing zipped doors.

The notch allows easy and hand-cutting. These adhesives have a very good hold from the very first seconds, and the more time passes, the harder they are to remove. Their adhesive mass works on dry and clean materials, therefore areas in contact with the tape must be cleaned to improve adhesion.

TECHNICAL TABLE

Item code	Width 48mm : TapeSH50W Width 96mm : TapeSH100W
Width x Length	2" x 108 ft / 4"x 108 ft 48 mm x 33 m / 96 mm x 33 m
Sales units	Box of 24 / Box of 12
Tape thickness	0,20mm = 200µ
Mechanical resistance	27 N/cm (breaking load)
Temperature resistance	-5°C to +50°C



EQUIPMENT SOLD SEPARATELY



RIPACK 3000



SAFETY CUTTERS



WIDE SHRINK-WRAP

